



Agilent 8347A, 8447A, and 8447D Amplifiers Data Sheet



RF & Microwave Amplifiers Specifications Summary for 8347A RF Amplifier (Discontinued) and 8447A/D Preamplifier

	8347A RF Amplifier (Discontinued)	8447A Preamplifier	8447D Preamplifier
Frequency range	100 kHz to 3 GHz	0.1 to 400 MHz	100 kHz to 1.3 GHz
Typical 3 dB bandwidth	—	50 kHz to 700 MHz	75 kHz to 1.7 GHz
Maximum leveled output power	≥ +20 dBm	—	—
Output power leveling range	(≥ 300 kHz): +2 to +20 dBm	—	—
Gain (mean, per channel)	≥ 25 dB	20 dB ± 1.0 dB at 10 MHz (20° to 30 °C)	> 25 dB (20° to 30 °C)
Gain flatness across full frequency range	Internally leveled ±300 kHz: ±1.5 dB	±1.8 dB (0° to 55 °C) ±0.7 dB (20° to 30 °C) characteristic	±1.5 dB
Noise figure	10 MHz to 3 GHz: 15 dB Below 10 MHz: 20 dB	< 7 dB	< 8.5 dB
Output power for 1 dB gain compression	+22 dBm	> +6 dBm	> +7 dBm typical
Third-order intercept	+30 dBm	—	—
Harmonic distortion	(at +20 dBm output) Internal level off (ALC off): ≤ -25 dBc	-32 dB for 0 dBm output Internal level on (ALC on): ≤ -20 dBc	-30 dB for 0 dBm output (typical)
Maximum input for minimum internally leveled output	-14 dBm	—	—
Output for <-60 dB harmonic distortion	—	-25 dBm (characteristic)	-30 dBm
VSWR	2.0: 1 input 1.5: 1 output internally leveled 2.0: 1 output unlevelled below 2 GHz 3.0: 1 output unlevelled 2 GHz to 3 GHz	< 1.7	< 2.0 input < 2.2 output 1 to 1300 MHz
Reverse isolation	60 dB	> 30 dB	> 40 dB
Maximum dc voltage output	—	±10 V	±10 V
Size	213 mm W x 102 mm H x 298 mm D (8.4 in x 4.0 in x 11.8 in)	130 mm W x 85.8 mm H x 261 mm D (5.1 in x 3.4 in x 8.5 in)	130 mm W x 85.8 mm H x 216 mm D (5.1 in x 3.4 in x 8.5 in)
Weight	Net, 4 kg (8 lb) Shipping, 5 kg (11 lb)	Net, 1.56 kg (3.4 lb) Shipping, 2.3 kg (5.1 lb)	Net, 1.56 kg (3.4 lb) Shipping, 2.3 kg (5.1 lb)
Power requirements	—	110 or 230 Vac + 10%, 48 to 440 Hz, 15 W	110 or 230 Vac + 10% 48 to 440 Hz, 15 W
Options available	—	Option 001: Dual-channel amp	Option 001: Dual-channel amp BNC (f) connectors Option 010: Single-channel amp Type-N (f) connectors Option 011: Dual-channel amp Type-N (f) connectors

Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Support is available for at least five years beyond the production life of the product. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you receive your new Agilent equipment, we can help verify that it works properly and help with initial product operation.

Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and onsite education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.

Agilent T&M Software and Connectivity

Agilent's Test and Measurement software and connectivity products, solutions and developer network allows you to take time out of connecting your instruments to your computer with tools based on PC standards, so you can focus on your tasks, not on your connections. Visit www.agilent.com/find/connectivity for more information.

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

www.agilent.com/find/contactus

Phone or Fax

United States:

(tel) 800 829 4444
(fax) 800 829 4433

Canada:

(tel) 877 894 4414
(fax) 800 746 4866

China:

(tel) 800 810 0189
(fax) 800 820 2816

Europe:

(tel) 31 20 547 2111

Japan:

(tel) (81) 426 56 7832
(fax) (81) 426 56 7840

Korea:

(tel) (080) 769 0800
(fax) (080)769 0900

Latin America:

(tel) (305) 269 7500

Taiwan:

(tel) 0800 047 866
(fax) 0800 286 331

Other Asia Pacific Countries:

(tel) (65) 6375 8100
(fax) (65) 6755 0042

Email: tm_ap@agilent.com

Contacts revised: 9/17/04

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2004
Printed in USA, September 24, 2004
5989-1696EN

